

IN THE CLAIMS:

Cancel Claims 2, 3, 4, 7, 8, 9, 16, 17, 20, and 21.

Amend Claims 1, 10, 11, 18, and 19, as follows:



1. (second amended) Removably attachable shielding
 2 to protect vehicle side surfaces and doors to prevent dents and
 scratches imposed by doors of adjacent vehicles, said shielding
 4 comprising:

RECEIVED
 MAR 05 2003
 GROUP 3600

two shield pads of impact absorbing material,
 at least one suction cup on each of said shield pads for
 removable attachment of the shield pad on a vehicle,

at least one strap secured to a lateral edge portion of
 each of said shield pads to connect them together,

an elastic strap having an end thereof secured to an edge
 portion of a first one of the shield pads, and

fastener means for detachably securing a second end portion
 of the elastic strap to a second one of the shield pads,

whereby the protective shields are removably attachable to
 vehicle sides and doors, and removable therefrom and rollable
 together. *side surfaces*

10. (first amended) Removably attachable shielding
2 to protect vehicle side surfaces and doors to prevent dents and
scratches imposed by doors of adjacent vehicles, said shielding
4 comprising:

two shield pads of impact absorbing material,

6 at least one suction cup on each of said shield pads
for removable attachment of the shield pad on a vehicle,

8 at least one strap secured to a lateral edge portion
of each of said shield pads to connect them together,

10 said shield pads and suction cups are adapted and
arranged for attachment to an interior surface of a vehicle
12 windshield to serve as a sunshade,

an elastic strap having an end thereof secured to an
14 edge portion of a first one of the shield pads, and

fastener means for detachably securing a second end
16 portion of the elastic strap to a second one of the shield pads,

whereby the protective shields are removably attachable
18 to vehicle sides and doors, and rollable up together.

11. (second amended) Removably attachable
shielding to protect vehicle side surfaces and doors to prevent
dents and scratches imposed by doors of adjacent vehicles, said
shielding comprising:

two shield pads of impact-absorbing material,

at least one suction cup on each of said shield pads
for removable attachment of the shield pad on a vehicle,

two spaced-apart straps extending between and secured
by lateral edge portions of the two shield pads,

an elastic strap having an end thereof secured to
an edge portion of a first one of the shield pads, and

fastener means for detachably securing a second end
portion of the elastic strap to a second one of the shield pads,

whereby the protective shields are removably attachable
to vehicle sides and doors, and removable therefrom and rollable
together.

18. (first amended) Removably attachable shielding

2 to protect vehicle side surfaces and doors to prevent dents and
scratches imposed by doors of adjacent vehicles, said shielding
4 comprising:

two shield pads of impact-absorbing material,

6 at least one suction cup on each of said shield pads
for removable attachment of the shield pad on a vehicle,

8 two spaced-apart straps extending between and secured
by lateral edge portions of the two shield pads,

10 said shield pads and suction cups being adapted and
arranged for attachment to an interior surface of a vehicle
12 windshield to serve as a sunshade,

14 an elastic strap having an end thereof secured to an
edge portion of a first one of the shield pads, and

16 fastener means for detachably securing a second end
portion of the elastic strap to a second one of the shield pads,

18 whereby the protective shields are removably attachable
to vehicle sides and doors, and rollable up together.

19. (second amended) Removably attachable
shielding to protect vehicle side surfaces and doors to prevent
dents and scratches imposed by doors of adjacent vehicles, said
shielding comprising:

two shield pads of impact-absorbing material,

at least one suction cup on each of said shield pads
for removable attachment of the shield pad on a vehicle,

at least one strap secured to a lateral edge portion
of each of said shield pads to connect them together,

an elastic strap having an end thereof secured to an
edge portion of a first one of the shield pads, said elastic
strap being attached to a central edge portion of one of the
shield pads and detachably securable to a central edge portion
of the other shield pad by one of (a) snap fasteners, (b) hook
and loop fasteners, and

fastener means for detachably securing a second end
portion of the elastic strap to a second one of the shield pads,

whereby the protective shields are removably attachable
to vehicle sides and doors, and removable therefrom and rollable
together.